



# Bowers & Wilkins

**703 S3**

Technical Information



<b>Technical features</b>	Decoupled Carbon Dome tweeter Solid Body Tweeter-on-Top Continuum™ cone FST™ midrange Decoupled midrange Aerofoil™ Profile bass cones Flowport™
<b>Description</b>	3-way vented-box system
<b>Drive units</b>	1x ø25mm (1in) Decoupled Carbon Dome high-frequency 1x ø150mm (6in) Continuum cone FST midrange 2x ø165mm (6.5in) Aerofoil profile bass
<b>Frequency range</b>	30Hz to 33kHz
<b>Frequency response</b> (+/-3dB from reference axis)	46Hz - 28kHz
<b>Sensitivity</b> (on axis at 2.83Vrms at 1m)	90dB
<b>Harmonic distortion</b>	2nd and 3rd harmonics (90dB, 1m on axis) <1% 90Hz - 22kHz <0.5% 120Hz - 20kHz
<b>Nominal impedance</b>	8Ω (minimum 3.1Ω)
<b>Recommended amplifier power</b>	30W - 200W into 8Ω on unclipped programme
<b>Max. recommended cable impedance</b>	0.1Ω
<b>Dimensions</b>	Height: 1010mm (39.8in) cabinet only 1117mm (44in) including tweeter and plinth  Width: 192mm (7.6in) cabinet only 290mm (11.4in) including plinth  Depth: 316mm (12.4in) cabinet only 353mm (13.9in) including grille and terminals 372mm (14.6in) including plinth
<b>Net weight</b>	28.8kg (63.5lbs)
<b>Finishes</b>	Cabinet: Gloss black Satin white Mocha Rosenut (APAC only)  Grille: Black Grey (Satin White only)