







See nothing, hear everything

The CCM7.3 S2 is a high-performance in-ceiling speaker for outstanding performance in both theatre and stereo applications. Its sophisticated drive unit configuration features a 25mm(1in) Carbon Dome tweeter, a 100mm (4in) FST™ Continuum cone midrange and 2 x 130mm (5in) Aerofoil Profile bass drivers. Its critically formed baffle is constructed from glass reinforced ABS while its integrated backbox ensures easy retrofittable installation, cuts down sound transfer between spaces and optimises sound quality.

Technical Specifications

Technical features	Carbon Dome tweeter Continuum cone FST midrange Aerofoil profile bass cones
Description	3-way in-ceiling system
Drive units	1x ø25mm (1in) Carbon Dome high-frequency 1x ø100mm (4in) Continuum cone FST midrange 2x ø130mm (5in) Aerofoil profile bass
Frequency range (-6dB)	-6dB at 52Hz and 33kHz
Frequency Response -3dB	55Hz - 28kHz ±3dB
Sensitivity	90dB spl (2.83Vrms, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 90Hz - 33kHz <0.5% 120Hz - 33kHz
Nominal impedance	8Ω (minimum 3.1Ω)
Recommended amplifier power	25W - 200W into 8Ω on unclipped programme
Frame height	355mm (14in)
Frame width	355mm (14in)
Depth	194.5mm (7.66in)
Cut-out height	332mm (13.1in)
Cut-out width	332mm (13.1in)
Cut-out height w/PMK	335mm (13.2in)
Cut-out width w/PMK	335mm (13.2in)
Protrusion	8mm (0.3in)
PMK	7C
Net weight	9kg (19.84lb) Inc accessories
Finishes	Back box: White Grille: White

FST, Continuum and Aerofoil are trademarks of B&W Group Ltd.

Copyright © B&W Group Ltd. E&OE